



竞阳条码  
JINGYANG BARCODE

111年7月20日 星期三

••••首页••关于公司••条码产品••条码知识••解决方案••联系我们

欢迎光临竞阳科技条码网站！我们将给您提供条码方面全面的信息！

••••条码打印机 •>>•美国zebra条码打印机• >> •Zebra TTP 2110条码打印机



•条码打印机  
•条码扫描器  
•数据采集器  
•条形码软件

•条码行业产品••

•条码打印机

美国Intermec条码打印机

日本Tec条码打印机

美国Zebra条码打印机

Zebra 110PAX4

Zebra EM220

Zebra Gx420d

Zebra HC100

Zebra Mz220

Zebra Mz320

Zebra P4T

Zebra R110PAX4

Zebra R110xi

Zebra R110xi HF

Zebra R170xi

Zebra R2844-Z

Zebra RP4T

Zebra Rw220

Zebra Rw420

Zebra Rz400

Zebra Rz600

•Zebra TTP 2110条码打印机



The TTP 2110 direct thermal printer is small enough to fit in the palm of your hand, yet robust enough for use in most ticketing applications, such as ATB1 boarding passes, bag tags, and tickets. By replacing traditional magnetic stripe technology with a simple linear or 2-D bar code, the TTP 2110 eliminates the costliest component in a ticketing system and offers a more economical alternative to traditional solutions. The automatic media detector makes it possible to load boarding passes or bag tags without adjustment. The ticket format is variable up to 82.5 mm/3.25" wide and 600 mm/23.6"long – so the TTP 2110 is ideal for printing ATB1 boarding passes, and IATA CUSS bag tags (with lengths up to 533 mm/21"). The TTP 2110 series' compact size makes the desktop version an attractive choice for both attended and unattended ticketing applications, while the embedded version fits neatly in kiosk designs.

Standard Features

RS-232 Serial Interface

Compact size 2-D bar coding

Media sensors - out-of-paper, paper in Presenter, top of form selectable for for or reflective settings, input for external paper-low sensor

Zebra TTP 2010	Prints ATB1 boarding passes, bag tags, and tickets
Zebra TTP 2020	Printer Specifications
Zebra TTP 2030	Resolution 203 dpi (8 dots/mm)
Zebra TTP 2110	Print width 2.13" (54 mm) for credit card size 3.15" (80 mm) for ATB1 size media
Zebra TTP 2130	Print length 23.6" (600 mm)
Zebra TTP 7030	Print speed 5.9" (150 mm)/sec
Zebra TTP 8200	Media Characteristics
Zebra TTP 8300	Maximum roll diameter 9.8" (250 mm)
Zebra888	Media thickness 0.004" (0.11 mm) to 0.01" (0.26 mm) for 2.13" (54 mm) paper
Zebra Z4M PLUS	Media types
Zebra 105SL	Roll or fanfold
Zebra Z6M PLUS	Operating Characteristics
Zebra 170XiIII PLUS	Operating temperature
Zebra 110XiIII PLUS	DT: Operating temperature 32° F (0° C) to 122° F (50° C) Direct thermal
Zebra 140XiIII PLUS	Storage temperatures 14° F (-10° C) to 122° F (50° C)
Zebra 220XiIII PLUS	Operating humidity 35-75% non-condensing R.H.
Zebra S600	Storage humidity 10-90% non-condensing excluding paper
Zebra 90XiIII	Electrical 24Vdc +/- 5% average 2A, peak 6A
Zebra 96XiIII	Physical Characteristics
Zebra TLP 2844	Width Embedded: 4.1" (105 mm) - Desktop: 4.5" (115 mm)
Zebra TLP 3842	Height Embedded: 2.6" - Desktop: 3.1" (Embedded: 65 mm - Desktop: 80 mm)
Zebra TLP 2742	Depth Embedded: 5.7" - Desktop: 7.1" (Embedded: 145 mm - Desktop: 180 mm)
Zebra TLP 3742	Weight Embedded: 2.4 lbs - Desktop: 3.1 lbs (Embedded: 1.1 kg - Desktop: 1.4 kg)
日本Sato条码打印机	Related Products
日本Ring条码打印机	Options
美国Datamax条码打印机	Print guides for 51, 54, 60, 66, 80 and 82.5 mm media
台湾Godex条码打印机	Leaf spring retainer for quick fit hubs
日本Toshiba条码打印机	Media holder (includes quick fit hubs and spring)
台湾TSC条码打印机	Paper-low sensor with 300 mm cable
韩国Woosim条码打印机	Output tray
德国CAB条码打印机	Communication and Interface Capabilities
	Serial RS232
	Windows 2000, XP, Server 2003, OPOS
	Bar Codes/Symbologies
	Linear
	EAN-8
	EAN-13
	UCC/EAN-128
	UPC

美国Printronix条码打印机

- 条码扫描器
- 数据采集器
- 无线局域网
- 条码标签
- 条码碳带
- 条码软件
- 条码检测仪
- 条码打印机配件
- **Rfid**电子标签

• 友情链接

- 
- 
- 
- 

••••• 销售热线

021—51088173•••••021—51088351



mail@gyoung.com.cn