



竞阳条码
gyoung

11年7月20日 星期三

••••• 首页 •• 关于公司 •• 条码产品 •• 条码知识 •• 解决方案 •• 联系我们

欢迎光临竞阳科技条码网站！我们将给您提供条码方面全面的信息！


••••• 条码打印机 •>>• 美国zebra条码打印机 • >> • Zebra TTP 8300条码打印机



• 条码打印机
• 条码扫描器
• 数据采集器
• 条形码软件

••

• Zebra TTP 8300条码打印机



• 条码行业产品 ••

• 条码打印机

美国Intermec条码打印机

日本Tec条码打印机

美国Zebra条码打印机

Zebra 110PAX4

Zebra EM220

Zebra Gx420d

Zebra HC100

Zebra Mz220

Zebra Mz320

Zebra P4T

Zebra R110PAX4

Zebra R110xi

Zebra R110xi HF

Zebra R170xi

Zebra R2844-Z

Zebra RP4T

Zebra Rw220

Zebra Rw420

Zebra Rz400

Zebra Rz600

The TTP 8300 series kiosk printers offer 300-dpi resolution for extremely sharp, full-format A4 or letter-size printouts of forms, bank statements, maps, or Web pages. The fast, compact, and low-maintenance design makes the printer ideal for unattended environments. The pull detector and jam-preventing loop presenter provide trouble-free operation. The retract function keeps sensitive documents from being left behind outside the kiosk—and it saves media. If a printout is not taken from the printer, the output will be retracted and the remaining information can be deleted from the print queue, eliminating unwanted print jobs. The TTP 8300 is available in three configurations for flexible kiosk integration: standard, compact, and vertical, each equipped with standard USB and parallel interfaces. For additional configuration flexibility, the media can be mounted either behind or below the printer.

Standard Features

USB and IEEE-1284 interfaces

Printer Specifications

Resolution 300 dpi (12 dots/mm)

Print width 8.5" (216 mm)

Print length Letter: 11" (279 mm) A4: 11.7" (297 mm)

Zebra TTP 2010	Print speed 2.60" (66 mm)/sec
Zebra TTP 2020	Media Characteristics
Zebra TTP 2030	Maximum roll diameter 9.84 (250 mm)
Zebra TTP 2110	Core diameter 1" (25 mm)
Zebra TTP 2130	Media thickness .002" (.054 mm) to .004" (.1 mm)
Zebra TTP 7030	Media types continuous, fanfold
Zebra TTP 8200	Operating Characteristics
Zebra TTP 8300	Operating temperature DT: Operating temperature 32° F (0° C) to 122° F (50° C) Direct thermal
Zebra888	Storage temperatures 4° F (-20° C) to 140° F (60° C)
Zebra Z4M PLUS	Operating humidity 35-75% non-condensing R.H.
Zebra 105SL	Storage humidity 10-90% non-condensing R.H.
Zebra Z6M PLUS	Electrical 24 VDC, ± 10%, average 6 A, peak 12 A
Zebra 170XiIII	Agency approvals UL cUL CE
PLUS	Physical Characteristics
Zebra 110XiIII	Width 11.3" (286 mm)
PLUS	Height 3.07" (78 mm)
Zebra 140XiIII	Depth 6.73" (171 mm)
PLUS	Weight 10.58 lbs (4.8 kg)
Zebra 220XiIII	Related Products
PLUS	Options
Zebra S600	Paper near end sensor
Zebra 90XiIII	weekend paper low sensor
Zebra 96XiIII	RS-232 Serial interface
Zebra TLP 2844	Communication and Interface Capabilities
Zebra TLP 3842	Parallel IEEE-1284 and USB
Zebra TLP 2742	Optional external RS-232 Serial
Zebra TLP 3742	Windows and Linux drivers. Direct addressing with ESC sequences.
日本Sato条码打印机	Bar Codes/Symbologies
日本Ring条码打印机	Linear
美国Datamax条码打印机	Code 39
台湾Godex条码打印机	Fonts and Graphics
日本Toshiba条码打印机	Up to eight bitmap fonts
台湾TSC条码打印机	
韩国Woosim条码打印机	
德国CAB条码打印机	

美国Printronix条码打印
机

- 条码扫描器
- 数据采集器
- 无线局域网
- 条码标签
- 条码碳带
- 条码软件
- 条码检测仪
- 条码打印机配件
- **Rfid**电子标签

• 友情链接

- •
- •
- •
- •

.....销售热线

021—51088173.....021—51088351



mail@gyoung.com.cn